



Contents

1. Product Overview


- 1-1. Model Naming Rule
- 1-2. NVR Line-up

2. Main features

- 2-1. Key Features Overview
- 2-2. Dark / White mode
- 2-3. Dynamic layout
- 2-4. Virtual channel monitoring
- 2-5. Section backup
- 2-6. User event [Manual trigger]


3. Specification

3-1. XRN-815S





1-1. Model Naming Rule






1-2. NVR Line-up

- Provides various products by HDD quantity, number of channels, and functions(AI, RAID, Redundant Power, PoE)
- Provides the same usability and improved functions/performance (NVR UI 2.0)

	~202	1			2022	
	1Q.21					
XRN-64	410B2					
XRN-64	10RB2					
XRN-32	210B2					
XRN-32	10RB2					
XRN-16	XRN-1620B2					
XRN-16	XRN-1620SB1					
XRN-8	320S					
		3Q.21		2Q.22		
	XRN-	420S		QRN-1630S		
	QRN-			QRN-830S		
			•	XRN-815S		

						Lilotel	NI - NI	
_						I : Intel,	IN : INOV	alek
	Model	Ch.	B/W	Resolution	HDDs	HDD size	RAID	CPU
	PRN-6400DB4	64	400	32M	16	10	0	1
	PRN-6400B4	64	400	32M	16	10	0	1
	PRN-3200B4	32	400	32M	16	10	0	- 1
	PRN-3200B2	32	400	32M	8	10	0	- 1
	PRN-1600B2	16	250	32M	8	10	0	- 1
	XRN-6410DB4	64	400	32M	16	10	0	1
	XRN-6410B4	64	400	32M	16	10	0	1
	XRN-3210B4	32	400	32M	16	10	0	1
	XRN-6410RB2	64	400	32M	8	10	0	1
	XRN-6410B2	64	400	32M	8	10	Χ	1
	XRN-3210RB2	32	400	32M	8	10	0	1
	XRN-3210B2	32	400	32M	8	10	Χ	1
	XRN-1620B2	16	140	32M	8	10	Χ	1
	XRN-1620SB1	16	140	32M	4	6	Χ	1
	XRN-820S	8	100	32M	2	6	Χ	I
	XRN-420S	4	50	8M	1	6	Χ	Ν
	XRN-815S	8	100	12M	2	10	Х	N
	QRN-1630S	16	128	8M	2	10	Χ	N
	QRN-830S	8	80	8M	1	6	Χ	N
	QRN-430S	4	40	8M	1	6	Χ	N





2-1. Key Features overview


- ❖ New Design look
- ❖ UI/UX 2.0
- Instant Viewer, Timeline pre-view, Event thumbnail view
- Dynamic layout, Virtual channel monitoring
- Compatible for Wisenet Al camera
- Improved for Wisenet camera compatibility(Thermal, PTZ, Multi)
- Support 'User Event' feature
- Al search(Person, Face, Vehicle : XRN-815S)
- * Bookmark management
- Section backup
- Improved 'Install wizard' (Set, Web)
- Compatible for ONVIF Profile S, RTP/RTSP
- Enhanced log up to 100,000 (System, Event each log)
- Enhanced P2P service for Mobile viewer





2-2. UI/UX 2.0 (New features)

User can change the GUI color to [Dark] or [White] mode




Dark Mode




2-3. Dynamic Layout

Convenient & Easy camera placement and tile layout changes



[Free layout]



[Expand / Reduce the tile]




2-4. Virtual channel monitoring

- NVR support the monitoring for un-registered virtual channels
- Virtual channel?
 - ► Camera function that provides multiple video channels such as fish-eye, multi-sensor cameras




[Multi-sensor Camera channels]





2-5. Section Backup


- User can backup the selected section on the playback timeline
- NVR support AVI format for export






2-6. User event [Manual trigger]

- User can make a specific event action with 'Manual trigger' function
- The event action require 'User coding'
 Ex) PTZ Wiper action, Camera I/O run, Camera B/W change





[Click the event trigger executes the SUNAPI command]





3-1. XRN-815S

		XRN-820S	XRN-815S		
Recording / Transmission B/W		120 / 120 Mbps	100 / 80 Mbps		
Compression		H.265, H.264, MJPEG			
Display		HDMI, VGA Dynamic Layout	HDMI 2EA Dynamic Layout		
Recording Resolution		CIF ~ 32 MP	CIF ~ 12 MP		
Event Trigger		Alarm Input, Video Loss, Camera Event, Dynamic Event, User Event			
Event Action		E-Mail, PTZ Preset, Alarm out, Buzzer, Monitor out, FTP, SUNAPI Command, Shutdown			
HDD slot		2 SATA, Support HDDs S.M.A.R.T			
Storage	HDD capacity	Up to 6 TB	Up to 10 TB		
Redundancy		Yes (ARB) / Failover(N+1)			
I/O		Alarm I/O 4 In 2 Out, USB 3EA (Front 2EA, Rear 1EA)			
Function		Dual Recording, Bookmark, Thumbnail view, Timeline control, P2P, Instant web browser('22.3Q)	Dual Recording, Bookmark, Thumbnail view, Timeline control, P2P		
PoE		8Port, Max. 100 W			
CPU		Intel Atom	Novatek (Comply with NDAA)		



