



SMT-2740

27" UHD monitor



Key Features

- 27 inch UHD Monitor, support up to 3840×2160@60Hz
- Brightness 300 cd/m² (Typical), Contrast 900:1 (Minimum), 1200:1 (Typical)
- Viewing Angle (H/V) : 178°/178°, Response Time : 14ms (Typical)
- Video Input : HDMI, DP, two windows PIP/PBP
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

SMT-2740

27" UHD monitor



Specifications

Display		
Type	LED Monitor	
Screen Size	27"	
Max. Resolution	3840*2160 60Hz (UHD)	
Brightness	300 cd/m² (Typ)	
Contrast Ratio	900:1 (Min) , 1200:1 (Typ)	
Aspect Ratio	16:9	
Viewing Angle (H/V)	178°/178°	
Display Color	1.07B Colors(Typ)	
Response Time	14ms(Typical)	
Panel Life	30,000 hours	
Interface		
Video	Connectors	HDMI 2.0(2), DP1.4(1), two windows PIP/PBP
HDMI	Connector	HDMI
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 2560 × 1440@60Hz,'3840×2160@60Hz, 3840 x 2160P@30/50/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
DP	Connector	DP
	Available Format	640 x 480@60Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz, 1024 x 768@60Hz/70Hz/75Hz, 1280 x 1024@60Hz/75Hz, 1440 x 900@60Hz, 1680 x 1050@60Hz, 1920 x 1080@50Hz/60Hz, 2560 × 1440@60Hz,'3840×2160@60Hz, 3840 x 2160P@30/50/60Hz, 720 x 480P60Hz, 1280 x 720P@50Hz, 720 x 576P@50Hz, 1920x1080P@50/60Hz, 1280 x 800@60Hz, 1280 x 960@60Hz, 1280 x 720@60Hz
Audio	Connector	Audio Out
	Output Signal	Loop-through line level(PC only), Speakers : 4Ω 2.5Wx 2
On Screen Display		
Functions	VESA™ DPM Compatible	
Language	Korean, English, Русский, Deutsch, Français, Español, Italiano, Português, Chinese (Simplified), Chinese (Traditional), Japanese, Arabic	
General		
Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	<45W

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com

Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions with Stand (WxHxD)	614.7*452.5*224.1mm
	Dimensions without Stand (WxHxD)	614.7*336.4*50.8mm
	Weight	5.04Kg(with stand), 4.63Kg(without stand)
	Cabinet Color	Black
	VESA Mounts Interface	100*100mm