

RG 59 B/U 75 Ω BLUE FOR OUTDOOR



www.bericacavi.com

Coaxial cables for video signal transmission, fire retardant, low halogens emission and UV resistant.

CEI UNEL
36762

1. Conductor
2. Insulation
3. Shield
4. Sheath



APPLICATION: Suitable for the connection between the camera and recorder in a closed-circuit television systems, that require more protection against the elements and in particular ultraviolet rays.

INSTALLATION: For fixed indoor and outdoor installation, without protection or in pipes, conduits and similar closed systems. They can be laid together with power cables with marking both 450/750V, and 0.6 / 1 kV, used for systems with a nominal voltage to ground (U₀) up to 400 V.

FEATURES	DESCRIPTION	STANDARD
Conductor :	copperweld	
Insulation :	polyethylene	
Shield :	braid of annealed red copper	
Sheath :	PVC , quality RZ	CEI EN 50363
Sheath colour :	blue RAL 5015 with red RAL 3000 row	
Fire retardant :		CEI 20-22/II
Low halogens emission :	(< 22%)	CEI EN 50267-2-1 - IEC 60754-1
Oil resistant :		CEI 20-34/0-1
UV resistant :		HD 605
DC resistance :	< 157,48 Ω/km	
Testing voltage :	2000 V	
Max working temperature :	70 °C	
Min. installation temperature :	0 °C	
Bending radius :	Ø x 14	
Printing :	BERICA CAVI S.P.A. ITALY Type CEI UNEL 36762 C-4 (U ₀ =400 V) CEI 20-22 O.R. UV RESISTANT CE Year/Lot	

ATTENUATION							
MHz	5	50	100	200	400	800	1000
dB/100 m	2,5	8,5	12	17,5	26	41,5	48,5

TYPE N° x mm	MEDIUM Ø OUTER mm	MEDIUM WEIGHT kg/km	PRODUCT CODE
1x0,58	6,0	43,0	B40RG59BLU