

Certificate of Conformity with European standards for Components and Systems

Number of Certificate

Valid from dd-mm-yyyy

Valid until dd-mm-yyyy

EN-ST-000303

07-03-2024

06-03-2028

Subject matter of Certificate:

Intruder control and indicating equipment grade 3 SPC53, SPC63 Upgrade, SPCP-G3

Owner of Certificate:

Vanderbilt International (IRL) Ltd. Clonshaugh Business & Technology Park IE-D17 KV84 DUBLIN 17

Basis for certification:

EN 50131-3:2009 EN 50131-6:2017 + A1:2021

Use, the product disposes of the following parameters:

Intrusion and hold-up systems, Grade 3 according to EN 50131-1

The tests were carried out at VdS Schadenverhütung GmbH and the results are documented in **test report**:

222310-AU01+STE04-PB01 dated 01-03-2024

A company of the German Insurance Association (GDV) accredited by DAkkS as certification body for fire protection and security products

VdS Schadenverhütung GmbH

Certification Body Amsterdamer Str. 174

D-50735 Köln

To guarantee the permanent quality of products a regular surveillance of the manufacturing process is performed.

This certificate comprises **4** pages and shall only be reproduced without any modifications and including all enclosures.

DAKKS

Deutsche
Akkreditierungsstelle
0-ZE-11149-01-04

Date: 07-03-2024

Managing director

p.p. Jeudmann

Head of certification body



Enclosure 1 Sheet 1

To Certificate No.: EN-ST-000303

Date: 07-03-2024

The approved component/system comprises the following parts:

Description of component	Туре	Applicant's Registration No.	Approval number of component (only complete for system approval)
Intruder and control equipment with a metal enclosure and build-in power supply (type A) providing the following common characteristics:	SPC53		
- 16 programmable areas			
- 128 hardwired zones (8 onboard)			
- 128 outputs (6 onboard)			
- Event memory 10000 intrusion events			
- 2 X-Bus interfaces			
- Max. 48 X-Bus devices			
- Build-in Power supply (Type A) for the I-CIE and auxiliary			
- Battery capacity 17 Ah / 12 V			
- Hardware Revision: A			
- Firmware Revision: V4.01			
- EN Grade 3			
- The internal Ethernet transmission path complies with SP6 of EN 50136-1			
Options:			
- License Upgrade	SPC63		
SPC53/SPC63 spare part PCB (For use in Vanderbilt SPC53 Product)	SPCP-G3		



Enclosure 2 Sheet 1

To Certificate No.: EN-ST-000303

Date: 07-03-2024

The approved component/system is described as follows:

Type of document	Manufacturer's identification	Date	Number of Pages
Installation Manual:	,		
- SPC Installation and Configuration (En)	I-200572	08.12.2023	297
- SPC Installation and Configuration (De)	I-200574	08.12.2023	325
- LCD Keypad SPCK620 / SPCK621 User Guide (En)	A6V10271018	01.10.2015	48
- LCD Keypad SPCK420 / SPCK421 User Guide (En)	A6V10209178	01.10.2015	38
- LCD Keypad SPCK520 / SPCK521 User Guide (En)	I-200004-1	01.10.2015	49
Technical Documents:			
- Circuit diagram	E-PC137032a SPC EVO Schematic.pdf	15.09.2023	17
- PCB Layout	E-PC137032a gerber.pdf	15.09.2023	13
- Bill of material	SPC42 BOM 15.09.23.xlsx	15.09.2023	*
- Label	SPC42 Rating label upgrade.pdf	07.03.2024	1
Datasheets:			
- Tactile Switch	KSC421G70SH-LFS.pdf	07.03.2024	3
- Tactile Switch	T6WM2RGQR.pdf	07.03.2024	3
- Tactile Switch	B3W-4050.pdf	07.03.2024	6
- Tactile Switch	DTSHW-24R-Q-TR.pdf	07.03.2024	4
- Relay	HFD16-12-ZFH-3.pdf	07.03.2024	3
- Relay	SRF-1C-SL-12VDC.pdf	07.03.2024	2
- Relay	V23101-D0106-A301.pdf	02/15	4
(*) Number of pages Printout dependent			



Enclosure 3 Sheet 1

To Certificate No.: EN-ST-000303

Date: 07-03-2024

Instructions for the application of the approval component/system (see enclosure 1):

- 1. The USB connector is approved for programming purposes only.
- 2. The device complies with Environmental Class II of EN 50130-5:2011.
- 3. The internal power supply complies with type A of EN 50131-6:2017 + A1:2021.
- 4. The device (Ethernet with GPRS backup) is suitable to provide alarm transmission according to category DP4 in line with EN 50136-1:2012 + A1:2018.
- 5. The device (Ethernet with PSTN backup) is suitable to provide alarm transmission according to category DP1 in line with EN 50136-1:2012 + A1:2018.
- 6. The device complies with EN 50130-4:2011 + A1:2014.