

MC 240

Contact magnétique, Montage encastré, NC

**Product :**






Montage	Recessed mounting
Circuit du contact	Normalement fermé (NF)
Certifications	EN 50131-2-6 Grade 2, Class IIIA, VdS G 193513 Class B, INCERT B-582-0013, SBSC 9-196, Class 1/2 , FG
Cote commutateur	48 VDC / 500 mA / 10 VA
Diamètre de perçage mm	9-10
Aimant (type)	Alnico 5
Installation sur bois	Only with accessories
Distance de fermeture (bois) mm	27
Distance de fermeture en mm (acier)	Depending from accessories used
Autoprotection	Oui
Connexion	Câble (connection de cable perpendiculaire)
Matériau du coffret	Al-alloy
Indice de protection	IP 67
Dimensions du commutateur (L x Ø) mm	37 x 11
Dimensions de l'aimant (L x Ø) mm	37 x 11
Température de fonctionnement	-40 - +70 °C
Grade	2

**Product description:**






Le modèle MC 240 est un contact à montage encastré. Il peut être utilisé pour tout type de systèmes de sécurité et de solutions industrielles de surveillance des portes et des fenêtres. La Fig.1 représente le schéma électrique d'une boucle d'alarme distincte et d'une boucle de sabotage. Nous proposons une large gamme d'accessoires d'installation permettant un montage encastré ou non, sur toute sorte de surface, y compris les matériaux ferromagnétiques.

Le MC 240 est certifié VdS classe B et répond aux exigences des normes EN 50131-2 6:2008 cat. 2 et IIIA.



Related products and accessories

	<p>MC 200-S3</p> <p>Plastic Housing for MC 240, 246 and 247</p>
	<p>MC 200-S11</p> <p>Plastic Flange for MC 240, 246, 247, 250, 255, 270, 272, 275</p>
	<p>MC 200-S12</p> <p>Plastic Flange with Strong Magnet for MC 240, 246, and 247</p>
	<p>MC 200-S21</p> <p>Plastic Snap-in Flange for MC 240, 246, 247, 250, 255, 270, 272, 275</p>
	<p>MC 200-S22</p> <p>Snap-in Flange with Strong Magnet for MC 240, 246 and 247</p>

Related products and accessories

	<p>MC 200-S31</p> <p>Plastic Snap-in Flange for MC 240, 246, 247, 250, 255, 270, 272, 275</p>
	<p>MC 200-S32</p> <p>Snap-in Flange with Strong Magnet for MC 240, 246, 247</p>
	<p>MC 200-4</p> <p>Aluminium Housing for MC 240, 246 and 247</p>
	<p>MC 200-5</p> <p>Aluminium Part with Extra Strong Magnet for MC 240, 246 and 247</p>
	<p>MC 200-6</p> <p>Aluminium Housing for Floor Installation for MC 240, 246 and 247</p>

Related products and accessories

	<p>MC 200-7</p> <p>Aluminium Housing for MC 240, 246 and 247</p>
	<p>MC 200-8</p> <p>Aluminium Part with Extra Strong Magnet for MC 240, 246 and 247</p>