

### Product description

Model with monitoring contact, actuated by the latch bolt.

### Overview of Advantages

- Water-proof for use outdoors
- Protection rating IP54 for the electrical components
- Connecting cable 300 mm length
- Equipped with bipolar protective diodes
- Radius keeper, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Striking plates with 2 position settings available
- Symmetrical design. DIN left/right as well as horizontal applicable

### Scope of delivery

- 1 piece electric strike

### Note

- Not an authorised locking system for doors along escape and rescue routes

### Technical data

|                                    |                         |
|------------------------------------|-------------------------|
| DIN-direction                      | universal               |
|                                    | 12 V DC                 |
| Adjustable keeper (FF, FaFix®)     | Yes                     |
| Monitoring contact (RR)            | Yes                     |
| Fail-unlocked                      | Yes                     |
| Bi-directional diode               | Yes                     |
| Rated resistance                   | 51 Ohm                  |
| Current consumption 12 V DC        | 235 mA                  |
| Break-in resistance                | 3750 N                  |
| Height                             | 67.3 mm                 |
| Width                              | 17.5 mm                 |
| Depth                              | 26 mm                   |
| FaFix® adjustment range            | 3 mm                    |
| Latch bolt engaging depth          | 5.5 mm                  |
| Operating temperature range        | -40 °C to +50 °C        |
| Installation position              | Vertical and horizontal |
| Load cycles for in-plant test      | 250000                  |
| Max. latch preload DC (stabilised) | 30 N                    |
| Article number                     | 138WR- - - - - E91      |
| EAN                                | 4042203650794           |

