

AXIS P3267-LVE Dome Camera

5 MP outdoor dome with IR and deep learning

Featuring Lightfinder 2.0, Forensic WDR, and OptimizedIR, AXIS P3267-LVE delivers excellent image quality under any light conditions. Built on an Axis system-on-chip (SoC), it includes a deep learning processing unit enabling advanced features and powerful analytics based on deep learning on the edge. For instance, AXIS Object Analytics, can detect and classify humans, vehicles, and types of vehicles, and enables fast VMS search. This robust, IK10-rated outdoor-ready camera includes Axis Edge Vault, a hardware-based cybersecurity platform that safeguards the devices and protects sensitive information from unauthorized access. Plus, AXIS P3267-LVE Mic features a built-in microphone, so it's out-of-the-box-ready for AXIS Audio Analytics.

- > [Excellent image quality in 5 MP](#)
- > [Lightfinder 2.0, Forensic WDR, and OptimizedIR](#)
- > [Analytics with deep learning](#)
- > [Variant with built-in microphone](#)
- > [Axis Edge Vault safeguards the device](#)



AXIS P3267-LVE Dome Camera

Camera

Variants

AXIS P3267-LVE
AXIS P3267-LVE Mic

Image sensor

1/2.7" progressive scan RGB CMOS

Lens

Varifocal, 3–8 mm, F1.3
Horizontal field of view: 104°–40°
Vertical field of view: 74°–29°
Minimum focus distance: 1 m (3.28 ft)
IR corrected, remote zoom and focus, P-Iris control

Day and night

Automatically removable infrared-cut filter

Minimum illumination

With Forensic WDR and Lightfinder 2.0:
Color: 0.13 lux at 50 IRE, F1.3
B/W: 0 lux at 50 IRE, F1.3

Shutter speed

1/33500 s to 1/5 s

Camera adjustment

Pan $\pm 190^\circ$, tilt -10 to $+80^\circ$, rotation $\pm 190^\circ$

System on chip (SoC)

Model

ARTPEC-8

Memory

2048 MB RAM, 8192 MB Flash

Compute capabilities

Deep learning processing unit (DLPU)

Video

Video compression

H.264 (MPEG-4 Part 10/AVC) Baseline, Main, and High Profiles
H.265 (MPEG-H Part 2/HEVC) Main Profile
Motion JPEG

Resolution

2592x1944 to 160x90

Frame rate

25/30 fps with power line frequency 50/60 Hz

Video streaming

Multiple, individually configurable streams in H.264, H.265, and Motion JPEG
Axis Zipstream technology in H.264 and H.265
Controllable frame rate and bandwidth
VBR/ABR/MBR H.264/H.265
Low latency mode
Video streaming indicator

Multi-view streaming

Up to 2 individually cropped out view areas in full frame rate

Image settings

Saturation, contrast, brightness, sharpness, Forensic WDR: up to 120 dB depending on scene, white balance, day/night threshold, local contrast, tone mapping, exposure mode, exposure zones, defogging, barrel distortion correction, compression, rotation: 0°, 90°, 180°, 270° including Corridor Format, mirroring, dynamic text and image overlay, privacy masks, polygon privacy mask

Pan/Tilt/Zoom

Digital PTZ, preset positions

Audio

Audio features

Automatic gain control
Speaker pairing
10-band graphic equalizer for audio input
Audio privacy control¹

Audio streaming

Two-way (full duplex)
Audio analytics still available when audio streaming is off¹

Audio input

External microphone input, line input, digital input with ring power or portcast technology
Built-in microphone (disabled by default): MEMS microphone¹

1. Only valid for variant with built-in microphone

Audio output

Output through speaker pairing or portcast technology

Audio encoding

24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz
Configurable bit rate

Microphone

SNR

66 dB(A) (94 dB SPL @ 1 m)²

Max SPL

129 dB (10% THD)²

Frequency range

20 Hz to 20 kHz, +/- 0.5 dB for analog mic/line input²

Network

Network protocols

IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS³, HTTP/2, TLS³, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP[®], SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTCP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

System integration

Application Programming Interface

Open API for software integration, including VAPIX[®] and AXIS Camera Application Platform; specifications at axis.com

One-click cloud connection

ONVIF[®] Profile G, ONVIF[®] Profile M, ONVIF[®] Profile S, and ONVIF[®] Profile T, specification at onvif.org

Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.

Video management software

Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms.

Onscreen controls

Day/night shift

Defogging

Wide dynamic range

Video streaming indicator

IR illumination

Edge-to-edge

Speaker pairing

Event conditions

Analytics, external input, supervised external input, virtual inputs through API

Call: state, state change

Device status: above operating temperature, above or below operating temperature, below operating temperature, within operating temperature, IP address removed, new IP address, network lost, system ready, ring power overcurrent protection, live stream active, casing open

Digital audio: digital signal contains Axis metadata, digital signal has invalid sample rate, digital signal missing, digital signal okay

Edge storage: recording ongoing, storage disruption, storage health issues detected

I/O: digital input, manual trigger, virtual input

MQTT: subscribe

Scheduled and recurring: schedule

Video: average bitrate degradation, day-night mode, live stream open, tampering

Event actions

Overlay text, external output activation, zoom preset, day/night mode, flash status LED, use lights, set defog mode, set WDR mode

Calls: end SIP call, make SIP call, answer call

I/O: toggle I/O once, toggle I/O while the rule is active

MQTT: publish

Notification: email, HTTP, HTTPS, TCP, and SNMP trap

Pre- and post-alarm video or image buffering for recording or upload

Record video: SD card and network share

Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email

Built-in installation aids

Remote zoom and focus, straighten image, pixel counter, level grid

2. Only valid for variant with built-in microphone

3. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).

Analytics

Applications

Included

AXIS Object Analytics, AXIS Scene Metadata, AXIS Image Health Analytics, AXIS Audio Analytics⁴, AXIS Live Privacy Shield⁵, AXIS Video Motion Detection, active tampering alarm, audio detection

Supported

AXIS Perimeter Defender, AXIS License Plate Verifier, AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap

AXIS Object Analytics

Object classes: humans, vehicles (types: cars, buses, trucks, bikes, other)

Scenarios: line crossing, object in area, time in area, crossline counting, occupancy in area, motion in area, motion line crossing

Up to 10 scenarios

Other features: triggered objects visualized with color-coded bounding boxes, polygon include/exclude areas, perspective configuration, ONVIF motion alarm event

AXIS Image Health Analytics

Detection settings:

Tampering: blocked image, redirected image

Image degradation: blurred image, underexposed image

Other features: sensitivity, validation period

AXIS Audio Analytics

Valid for variant with built-in microphone

Features: adaptive audio detection, audio classification

Audio classes: scream, shout, glass break, speech

Event metadata: audio detections, classifications

AXIS Scene Metadata

Object classes: humans, faces, vehicles (types: cars, buses, trucks, bikes), license plates

Object attributes: vehicle color, upper/lower clothing color, confidence level, position

Audio data: audio level

Approvals

EMC

EN 50121-4, EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2

Australia/New Zealand: RCM AS/NZS CISPR 32 Class A

Canada: ICES-3(A)/NMB-3(A)

Japan: VCCI Class A

Korea: KC KN32 Class A, KC KN35

USA: FCC Part 15 Subpart B Class A

Railway: IEC 62236-4

Safety

CAN/CSA C22.2 No. 62368-1 ed. 3,

IEC/EN/UL 62368-1 ed. 3, IEC/EN 62471, IS 13252

Environment

IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9)

Network

NIST SP500-267

Cybersecurity

ETSI EN 303 645, BSI IT Security Label, FIPS-140

Cybersecurity

Edge security

Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 Client Credential Flow/OpenID Authorization Code Flow for centralized ADFS account management, password protection, Axis Cryptographic Module (FIPS 140-2 level 1), AES-XTS-Plain64 256bit SD card encryption

Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), system-on-chip security (TEE), Axis device ID, secure keystore, signed video, secure boot, encrypted filesystem (AES-XTS-Plain64 256bit)

Network security

IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2)⁶, IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS⁶, TLS v1.2/v1.3⁶, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall

4. Only valid for variant with built-in microphone

5. Available for download

6. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).

Documentation

AXIS OS Hardening Guide

Axis Vulnerability Management Policy

Axis Security Development Model

AXIS OS Software Bill of Material (SBOM)

To download documents, go to axis.com/support/cybersecurity/resources

To read more about Axis cybersecurity support, go to axis.com/cybersecurity

General

Casing

IP66-, NEMA 4X- and IK10-rated

Polycarbonate hard coated dome

Polycarbonate casing and weathershield

Color: white NCS S 1002-B

For repainting instructions, go to the product's support page. For information about the impact on warranty, go to axis.com/warranty-implication-when-repainting.

Mounting

Mounting bracket with junction box holes (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount

Power

Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3

Typical 6.4 W, max 12.1 W

Connectors

Network: RJ45 10BASE-T/100BASE-TX PoE

I/O: 4-pin 2.5 mm (0.098 in) terminal block for 1 supervised digital input and 1 digital output (12 V DC output, max. load 25 mA)

Audio: 3.5 mm mic/line in

IR illumination

Optimized IR with power-efficient, long-life 850 nm IR LEDs

Range of reach 40 m (130 ft) or more depending on the scene

Storage

Support for microSD/microSDHC/microSDXC card

Support for SD card encryption (AES-XTS-Plain64 256bit)

Recording to network-attached storage (NAS)

For SD card and NAS recommendations see axis.com

Operating conditions

Temperature: -40 °C to 50 °C (-40 °F to 122 °F)

Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F)

Start-up temperature: -30 °C to 50 °C (-22 °F to 122 °F)

Humidity: 10–100% RH (condensing)

Storage conditions

Temperature: -40 °C to 65 °C (-40 °F to 149 °F)

Humidity: 5–95% RH (non-condensing)

Dimensions

Without weathershield:

Height: 107 mm (4.21 in)

Ø 149 mm (5.87 in)

Weight

With weathershield:

900 g (2.0 lb)

Box content

Camera, installation guide, Windows® decoder 1-user license, drill template, RESISTORX® T20 screw bit, terminal block connectors, cable gaskets, connector guard, weathershield

Optional accessories

AXIS TP3201-E Recessed Mount, AXIS TP3103-E

Pendant Kit, AXIS T8355 Digital Microphone 3.5 mm,

AXIS TP3824-E Dome Clear/Smoked, AXIS TP3821-E

Casing Black/White, AXIS Surveillance Cards

For more accessories, see axis.com

Languages

English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese

Warranty

5-year warranty, see axis.com/warranty

Sustainability

Substance control

PVC free, BFR/CFR free in accordance with JEDEC/ECA Standard JS709

RoHS in accordance with EU RoHS Directive 2011/65/EU/ and EN 63000:2018

REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see echa.europa.eu

Materials

Renewable carbon-based plastic content: 6.5%
(recycled)

Screened for conflict minerals in accordance with OECD
guidelines

To read more about sustainability at Axis, go to [axis.com/about-axis/sustainability](https://www.axis.com/about-axis/sustainability)

Environmental responsibility

[axis.com/environmental-responsibility](https://www.axis.com/environmental-responsibility)

Axis Communications is a signatory of the UN Global
Compact, read more at unglobalcompact.org