

AXIS P7304 Video Encoder

Full-featured, 4-channel video encoder with HD analog support

AXIS P7304 is a full-featured, 4-channel video encoder that adds the benefits of IP surveillance to any analog camera system. It supports standard and HD analog cameras up to 4K resolution, and analog PTZ cameras. Enhanced security features such as signed firmware and secure boot ensure the integrity and authenticity of the encoder's firmware. Plus, Zipstream with support for H.264/H.265 video compression significantly reduces bandwidth and storage requirements. The encoder features two-way audio, I/O ports, and a memory card slot for edge storage. It also comes with intelligent analytics such as motion detection, audio detection and tampering alarm.

- > [Support for HD analog cameras up to 4K](#)
- > [PTZ control](#)
- > [2-way audio and configurable I/O](#)
- > [Zipstream with support for H.264/H.265](#)
- > [Signed firmware and secure boot](#)



AXIS P7304 Video Encoder

System on chip (SoC)

Model
ARTPEC-7

Memory
1024 MB RAM, 512 MB Flash
Battery backed-up real-time clock

Video

Video compression
H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles
H.265 (MPEG-H Part 2/HEVC) Main Profile
Motion JPEG

Resolution
176x144/176x120 (PAL/NTSC) to 720x576/720x480 (PAL/NTSC). Also high definition TVI, high definition CVI and high definition analog HD (1280x720 and 1920x1080)
One channel for resolutions above 1080p (1920x1080)¹

Frame rate
25/30 fps in all resolutions up to 1080p
Up to 30 fps in quad view in full resolution 1080p
One channel Quad HD up to 25/30 fps
One channel 4K up to 15 fps

Video streaming
Multiple, individually configurable streams in H.264, H.265 and Motion JPEG
Axis Zipstream technology in H.264 and H.265
Controllable frame rate and bandwidth
VBR/MBR H.264/H.265
Quad view

Image settings
Compression, color, brightness, contrast, rotation: 0°, 90°, 180°, 270°, aspect ratio correction, mirroring of images, text and image overlay, privacy mask, enhanced deinterlace filter, video termination, anti-aliasing, sharpness, noise reduction, local enhancement

Pan/Tilt/Zoom

Wide range of analog PTZ cameras supported, drivers included in the firmware
Up to 100 preset positions/camera, Guard tour, PTZ control queue
Supports Windows compatible joysticks
Compatible with Coaxitron® by Pelco

Audio

Audio encoding
24bit LPCM, AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz
Configurable bit rate

Audio input/output

Two analog or digital external microphone input or line input, line output.

Network

IP address
One IP address for four channels

Security
IP address filtering, HTTPS² encryption, IEEE 802.1X² network access control, user access log, centralized certificate management

Network protocols
IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS², TLS², QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

1. When you enable one channel for resolutions above 1080p (1920x1080), it disables channel 3.
2. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).

System integration

Application Programming Interface

Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com

AXIS Video Hosting System (AVHS) with One-Click Camera Connection

One-click cloud connection

ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S and ONVIF® Profile T, specification at onvif.org

Video management systems

Compatible with AXIS Camera Station Edge, AXIS Camera Station Pro, AXIS Camera Station 5, and video management software from Axis' partners available at axis.com/vms.

Event triggers

Analytics, video loss, edge storage events
MQTT subscribe

Event actions

File upload: FTP, SFTP, HTTP, HTTPS network share and email

Notification: email, HTTP, HTTPS and TCP

External output activation

MQTT publish

Pre- and post-alarm video buffering

PTZ preset

Status LED

Data streaming

Event data

Analytics

Applications

Included

AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, AXIS Video Motion Detection
Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap

Cybersecurity

Edge security

Software: Signed OS, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 Client Credential Flow/OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption

Hardware: Secure boot

Network security

IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2)³, IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS³, TLS v1.2/v1.3³, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall

Documentation

AXIS OS Hardening Guide

Axis Vulnerability Management Policy

Axis Security Development Model

AXIS OS Software Bill of Material (SBOM)

To download documents, go to axis.com/support/cybersecurity/resources

To read more about Axis cybersecurity support, go to axis.com/cybersecurity

General

Casing

Stand alone, metal casing, wall mount

Sustainability

PVC free

Power

8-28 V DC, max 8.2 W Power over Ethernet (PoE)

IEEE 802.3af/802.3at Type 1 Class 3

Connectors

Four analog composite video BNC input

RJ45 10BASE-T/100BASE-T/1000 BASE-T PoE

6-pin 2.5 mm I/O terminal block with four configurable inputs and outputs

2 pcs 3.5 mm mic/line in, 1 pcs 3.5 mm line out

RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block

3. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Storage

Support for microSD/microSDHC/microSDXC card
Support for SD card encryption (AES-XTS-Plain64
256bit)

Support for recording to network-attached storage
(NAS)

For SD card and NAS recommendations see axis.com

Operating conditions

0 °C to 50 °C (32 °F to 122 °F)

Humidity 10-85% RH (non-condensing)

Storage conditions

-40 °C to 65 °C (-40 °F to 149 °F)

Humidity 5-95% RH (non condensing)

Approvals

EMC

EN 55032 Class A, EN 61000-3-2, EN 61000-3-3,
EN 55024, EN 61000-6-1, EN 61000-6-2,
FCC Part 15 Subpart B Class A, ICES-003 Class A,
VCCI Class A, RCM AS/NZS CISPR 32 Class A,
KC KN32 Class A, KC KN35

Safety

IEC/EN/UL 62368-1

Environment

IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6,
IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78

Network

NIST SP500-267

Dimensions

187 x 37 mm (7.4 x 1.5 in)

Weight

650 g (1.4 lb)

Included accessories

Installation guide, Windows® decoder 1-user license, DC
input plug, 6-pin I/O plug, 2 pcs 2-pin RS485/RS422
plugs

Optional accessories

For more accessories, see axis.com

Languages

English, German, French, Spanish, Italian, Russian,
Simplified Chinese, Japanese, Korean, Portuguese,
Traditional Chinese, Dutch, Czech, Swedish, Finnish,
Turkish, Thai, Vietnamese

Warranty

5-year warranty, see axis.com/warranty