



Aperio E100 electronic fitting

Online Wireless – Premium



Overview of Advantages

- Material: Stainless steel
- Protection class: IP54*
- Power supply: Battery
- Battery service life: approx. 40,000 actuations or 2 years
- Reader method: contact-free
- Temperature range: -25 to +60°*
- Interface: wireless via HUB to DoorController
- Operability: Online
- *Please note that adverse environmental conditions can impair the functionality of the product (excessive humidity, salt, external temperatures)

Product description

- Aperio C100 electronic wireless fitting with integrated reader module for online applications in Premium version.
- Requires a wireless hub and a door controller with Aperio firmware.
- Operation via battery.
- Authorisation is granted via the door controller and is requested from the end device by the wireless hub.

Scope of delivery

- 1 Fitting incl. electronics and antenna
- 1 Fastening set
- 1 battery CR123A
- 1 Drilling template carton

Note

- Requires Door-Controller
- Requires Wireless Hub
- Requires k-entry 6.0

Special equipment

5011 B/B/9/K/X/X/X/-/-

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

1: ID-Modul	B: RFID IP54
2: Reader method	B: Multi RFID Legic Advant & Mifare Desfire C:
3: Spindle	9: 9 mm
4: Door thickness	K: 40 - 44 mm L: 45 - 49 mm M: 50 - 54 mm N: 55 - 59 mm O: 60 - 64 mm P: 65 - 69 mm Q: 70 - 74 mm R: 75 - 79 mm S: 80 - 84 mm T: 85 - 89 mm U: 90 - 94 mm V: 95 - 99 mm
5: Cylinder cutout	-: Blind outside and inside 1: Euro outside and inside 3: Swiss outside and inside 5: Swiss outside, blind inside 6: Euro outside, blind inside

6: Centres distance

7: Handle

8: Protocol

9: Privacy

Variants that can be ordered

Order number	Product
5011	Aperio E100 electronic fitting 5011